



◆ SPECIFICATION

Model NO.	AC53
<b>Camera</b>	
Image Sensor	1/3"CMOS sensor
Resolution	5MP
Effective Pixels	2560(H)*1920(V)
Compression	H.265
Electronic Shutter Time	Auto ( 1 / 12s~1 / 100000s )
S/N Ratio	40dB
Scanning System	Progressive
Video Output	Wireless network
Reset Button	Yes
<b>PTZ</b>	
Horizontal Rotation Range	0~270°
Tilt Rotation Range	0~90°
Guard Points	Optional,Max 6 points
<b>LENS Type</b>	
Focus Length	4mm F2.0
Focus Control	Fixed
Lens Type	Fixed
Pixels	3M Pixels
<b>Night Vision</b>	
Infrared LED	4 pcs Infrared lamp + 4 pcs LED lamp beads

Infrared Distance	10-15m (Depending On Environment)
IR Status	CDS Auto Control
IR Power On	Auto Control
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP、UDP、HTTP、DDNS、DHCP、FTP、NTP
ONVIF	Optional
P2P	Support
4G	/
POE	/
Main Stream 1	2304*1296@20fps
Main Stream 2	/
Main Stream 3	/
Sub Stream 1	640*360@20fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	/
IE Brower	/
Smart Phone	support
<b>Wireless</b>	
Antenna	3dbi
Hotspot	Support
Wi-Fi	Wi-Fi(IEEE802.11b/g/n)
WIFI Range	No obstacles 350m Max.
<b>Camera Features</b>	
Day/Night	Color/ B&W (IR-CUT )
Minimun Illumination	0.01 Lux
Image Config	YES
Corridor Pattern	/
ROI	/
Defog Mode	/
BLC	/

HDR	/
3DNR	Support
DWDR	Support
Motion Detection	Support
Privacy Masking	/
Recording Mode	SDcard
Language	Chinese, English

## Function

Audio	2-Way Audio
Alarm	Motion Detection
SD Card Slot	Support Max 128G

## General

Housing	plastic, IP65
Bracket	Support
IR Cut Filter	YES
Power	DC 12V/1A
Operation Temperature	-10°C ~ +50°C RH75% Max
Storage Temperature	-20°C ~ +60°C RH75% Max
Size	166(D)×98(W)×233(H)mm

### Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: [info@cantonk.com](mailto:info@cantonk.com)