



◆ SPECIFICATION

Model NO.	IPR25FK500W
Camera	
Image Sensor	1/2.5" High-resolution CMOS Sensor
Resolution	5MP
Effective Pixels	2608(H)*1952(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
Minimum Illumination	0.01Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Reset Button	NO
LENS Type	
Focus Length	Board Lens 3.6mm/F2.0
Focus Control	Fixed
Lens Type	Fixed
Pixels	5MP
Night Vision	
Infrared LED	42μx 2PCS
Infrared Distance	25M
IR Status	Auto

IR Power On	Auto
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP, UDP
ONVIF	Support ONVIF 2.4(Profile S/T/G)
P2P	YES, Support QR Code
POE	/
Video Delay	0.3S (Within the Lan)
Main Stream 1	2592*1944@20fp 2560*1920@20fp
Main Stream 2	2560*1440@30fp
Main Stream 3	1920*1080@30fps
Sub Stream 1	720*480@20fps 720*480@30fps
Sub Stream 2	352*288@20fps 352*288@30fps
Sub Stream 3	/
Tri Stream	/
IE Brower	IE8-11, Google Chrome, Firefox , Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
Wireless	
Antena	3dbi
Hotspot	/
Wi-Fi	Wi-Fi(IEEE802.11b/g/n),2.4Ghz
WIFI Range	No obstacles 300m Max.
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Corridor Pattern	Support
ROI	/
Defog Mode	Support
BLC	Support
HDR	/
WDR	/
Motion Detection	Support

Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/VMS/Web/SD Card
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Netherlands, Czech, Vietnamese
Interface	
Audio	Optional Audio in by Line(RCA interface)
Alarm	/
SD Card Slot	support 256G Micro SD With External SD Card Slot
RS485	/
General	
Housing	Metal, IP67
Anti-cut Bracket	Anti-Cut 3-Axis
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 700mA
Dimension	157(W) x 70(H) x 66(D)mm
Weight	650g

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com