

# KBL-PB

Bullet Cameras

Lens:3.7mm Taper Pinhole Lens

Dimension:∅ 20 x 62(H) mm

Weight:250g



Model	KBL-227PB	KBL-405PB
Image Sensor	1/4"SONY	1/3"SONY
TV System	PAL/NTSC	
Horizontal Resolution	420 TV Line	420 TV Line
Pixels	PAL:795(H)× 596(V) NTSC:811(H)× 508(V)	PAL:500(H)× 582(V) NTSC:510(H)× 492(V)
IR LED		
IR Series Distance		
Lens	3.7mm Taper Pinhole Lens	
Sync System	Internal	
IR Status	Under 10 Lux By CDS	
S/N Ratio	≥ 48dB (AGC OFF)	
Gamma Correction	0.45	
Video Out	Composite Signal (1.0Vp-p, 75Ω)	
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec	
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec	
Operation Temperature	-10°C ~ +50°C RH95% Max	
Storage Temperature	-20°C ~ +60°C RH95% Max	
White Balance	Auto	
Power Source	DC12V 150mA	
Dimension	∅ 20 x 62(H) mm	
Weight	250g	