

# KDV-DT45

Vandalproof Dome Camera

SONY/SHARP CCD

3-Axis bracket built-in

Lens: 4-9mm Manual Zoom Lens USD2 extra for 2.8-12mm Manual Zoom Lens

Dimension:  $\varnothing$  140x 94(H) mm Weight: 700g



Model	KIR-2362DT45	KIR-633DT45	KIR-2421DT45	
Image Sensor	1/3"SONY	1/3"SONY	1/4"SHARP	
TV System	PAL/NTSC			
Horizontal Resolution	560TV Lines Low Illumination	420TV Lines Low Illumination	420 TV Line Low Illumination	
Pixels	PAL:752(H)× 582(V) NTSC:768(H)× 494(V)	PAL:500(H)× 582(V) NTSC:510(H)× 492(V)		
IR LED				
IR Series Distance				
Lens	4-9mm Manual Zoom Lens			
Sync System	Internal			
IR Status	Under 10 Lux By CDS			
IR Power On	CDS Auto Control			
Usable Illumination	0.001 Lux/F2.0	0.0005Lux/F2.0	0.01 Lux/F2.0	0.01 Lux/F2.0
S/N Ratio	$\geq$ 48dB (AGC OFF)			
Gamma Correction	0.45			
Video Out	Composite Signal (1.0Vp-p, 75 $\Omega$ )			
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec			
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec			
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max			
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max			
White Balance	Auto			
Power Source	DC12V 350mA			
Dimension	$\varnothing$ 140 x 94(H) mm			
Weight	700g			