

KDV-SH20

Vandalproof IR Dome Camera

IR LED: \varnothing 5X24PCS IR LED working distance: 20M

Lens: Board Lens 3.6mm/F2.0

Dimension: \varnothing 94 x 69(H) mm Weight: 400g



Model	KDV-2362SH20	KDV-633SH20	KDV-2421SH20	KDV-1030SH20
Image Sensor	1/3"SONY	1/3"SONY	1/4"SHARP	1/4"CMOS
TV System	PAL/NTSC			
Horizontal Resolution	560TV Lines Low Illumination	420TV Lines Low Illumination	420 TV Line Low Illumination	480TV Lines Low
Pixels	PAL:752(H) \times 582(V) NTSC:768(H) \times 494(V)	PAL:500(H) \times 582(V) NTSC:510(H) \times 492(V)		
IR LED	\varnothing 5X24PCS			
IR Series Distance	20M			
Lens	Board Lens 3.6mm/F2.0			
Sync System	Internal			
IR Status	Under 10 Lux By CDS			
IR Power On	CDS Auto Control			
Usable Illumination	0.001 Lux/F2.0	0.0005 Lux/F2.0	0.01 Lux/F2.0	0.01 Lux/F2.0
S/N Ratio	\geq 48dB (AGC OFF)			
Gamma Correction	0.45			
Video Out	Composite Signal (1.0Vp-p, 75 Ω)			
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec			
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec			
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max			
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max			
White Balance	Auto			
Power Source	DC12V 350mA			
Dimension	\varnothing 94 x 69(H) mm			
Weight	400g			