

KDV-KR45

4.5" Vandalproof Dome Camera

IR LED: \varnothing 5X21PCS IR LED working distance: 20M

3-Axis bracket built-in

Lens:4-9mm Manual Zoom Lens USD2 extra for 2.8-12mm Manual Zoom Lens

Dimension : \varnothing 149x 99(H) mm Weight:1kg

Model	KIR-2362KR45	KIR-633KR45	KIR-2421KR45
Image Sensor	1/3"SONY	1/3"SONY	1/4"SHARP Low Illumination
TV System	PAL/NTSC		
Horizontal Resolution	560TV Lines Low Illumination	420TV Lines Low Illumination	420 TV Line Low Illumination
Pixels	PAL:752(H) \times 582(V) NTSC:768(H) \times 494(V)	PAL:500(H) \times 582(V) NTSC:510(H) \times 492(V)	
IR LED			
IR Series Distance			
Lens	4-9mm Manual Zoom Lens		
Sync System	Internal		
IR Status	Under 10 Lux By CDS		
IR Power On	CDS Auto Control		
Usable Illumination	0.001 Lux/F2.0	0.0005Lux/F2.0	0.01 Lux/F2.0
S/N Ratio	\geq 48dB (AGC OFF)		
Gamma Correction	0.45		
Video Out	Composite Signal (1.0Vp-p, 75 Ω)		
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec		
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec		
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max		
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max		
White Balance	Auto		
Power Source	DC12V 350mA		
Dimension	\varnothing 149x 99(H) mm		
Weight	1000g		