

KDP-S25

Plastic Dome Camera

SONY/SHARP CCD

Lens: 3.6mm Board lens/F2.0

Dimension : \varnothing 87.5 x 58(H) mm

Weight:300g



Model	KIR-1030S25	KIR-2362S25	KIR-633S25	KIR-2421S25
Image Sensor	1/4"CMOS	1/3"SONY	1/3"SONY	1/4"SHARP
TV System	PAL/NTSC			
Horizontal Resolution	480 TV Line	560 TV Line Low Illumination	420 TV Line	420 TV Line
Pixels	PAL:500(H)×582(V) NTSC:510(H)×492(V)	PAL:795(H)×596(V) NTSC:811(H)×508(V)	PAL:500(H)×582(V) NTSC:510(H)×492(V)	PAL:500(H)×582(V) NTSC:510(H)×492(V)
IR LED				
IR Series Distance				
Lens	3.6mm Board lens/F2.0			
Sync System	Internal			
IR Status	Under 10 Lux By CDS			
IR Power On	CDS Auto Control			
Usable Illumination	0.01 Lux/F2.0	0.001 Lux/F2.0	0.0005Lux/F2.0	0.001 Lux/F2.0
S/N Ratio	≥ 48dB (AGC OFF)			
Gamma Correction	0.45			
Video Out	Composite Signal (1.0Vp-p, 75Ω)			
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec			
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec			
Operation Temperature	-10°C ~ +50°C RH95% Max			
Storage Temperature	-20°C ~ +60°C RH95% Max			
White Balance	Auto			
Power Source	DC12V 150mA			
Dimension	\varnothing 87.5 x 58(H) mm			
Weight	300g			