

# KDP-SH25

Plastic Dome Camera with 360 degrees Rotation

SONY/SHARP CCD

IR LED:  $\varnothing$  5X30PCS IR LED working distance: 25M

Lens: 3.6mm Board lens/F2.0

Dimension :  $\varnothing$  100 x 70(H) mm

Weight:300g



Model	KDP-2362SH25	KDP-633SH25	KDP-2421SH25	KDP-1030SH25
Image Sensor	1/3"SONY	1/3"SONY	1/4"SHARP	1/4"CMOS
TV System	PAL/NTSC			
Horizontal Resolution	560 TV Line Low Illumination	420 TV Line Low Illumination	420 TV Line Low Illumination	480 TV Line
Pixels	PAL:795(H) $\times$ 596(V) NTSC:811(H) $\times$ 508(V)		PAL:500(H) $\times$ 582(V) NTSC:510(H) $\times$ 492(V)	PAL:500(H) $\times$ 582(V) NTSC:510(H) $\times$ 492(V)
IR LED	$\varnothing$ 5X30PCS IR LED			
IR Series Distance	25M			
Lens	3.6mm Board lens/F2.0			
Sync System	Internal			
IR Status	Under 10 Lux By CDS			
IR Power On	CDS Auto Control			
Usable Illumination	0.001 Lux/F2.0	0.0005 Lux/F2.0	0.01 Lux/F2.0	0.01 Lux/F2.0
S/N Ratio	$\geq$ 48dB (AGC OFF)			
Gamma Correction	0.45			
Video Out	Composite Signal (1.0Vp-p, 75 $\Omega$ )			
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec			
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec			
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max			
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max			
White Balance	Auto			
Power Source	DC12V 150mA			
Dimension	$\varnothing$ 100 x 70(H) mm			
Weight	300g			