

# KDV-SN20

Vandalproof IR Dome Camera

IR LED:  $\varnothing$  5X24PCS IR LED working distance: 20M

Lens: Board Lens 3.6mm/F2.0

Dimension:  $\varnothing$  94 x 69(H) mm Weight:450g



Model	KDV-639SN20	KDV-409SN20	KDV-405SN20	KDV-2421SN20
Image Sensor	1/3"SONY	1/3"SONY	1/3"SONY	1/3"SHARP
TV System	PAL/NTSC			
Horizontal Resolution	540 TV Line Low Illumination	540 TV Line	420 TV Line	420 TV Line
Pixels	PAL:795(H)×596(V) NTSC:811(H)×508(V)		PAL:500(H)×582(V) NTSC:510(H)×492(V)	PAL:500(H)×582(V) NTSC:510(H)×492(V)
IR LED	$\varnothing$ 5X24PCS			
IR Series Distance	20M			
Lens	Board Lens 3.6mm/F2.0			
Sync System	Internal			
IR Status	Under 10 Lux By CDS			
IR Power On	CDS Auto Control			
Usable Illumination	0 Lux/F2.0 (LED ON)			
S/N Ratio	$\geq$ 48dB (AGC OFF)			
Gamma Correction	0.45			
Video Out	Composite Signal (1.0Vp-p, 75 $\Omega$ )			
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec			
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec			
Operation Temperature	-10°C ~ +50°C RH95% Max			
Storage Temperature	-20°C ~ +60°C RH95% Max			
White Balance	Auto			
Power Source	DC12V 350mA			
Dimension	$\varnothing$ 94 x 69(H) mm			
Weight	450g			