

KHD-SP2

PIR Spy Camera

Back Light Compensation(BLC)

Lens: 3.7mm Taper Pinhole Lens

Dimension : 70(W) x40(H) x119(D)mm Weight:300g



Model	KHD-639SP2	KHD-409SP2	KHD-405SP2	KHD-2421SP2
Image Sensor	1/3"SONY	1/3"SONY	1/3"SONY	1/3"SHARP
TV System	PAL/NTSC			
Horizontal Resolution	540 TV Line Low Illumination	540 TV Line	420 TV Line	420 TV Line
Pixels	PAL:795(H)×596(V) NTSC:811(H)×508(V)		PAL:500(H)×582(V) NTSC:510(H)×492(V)	PAL:500(H)×582(V) NTSC:510(H)×492(V)
IR LED				
IR Series Distance				
Lens	3.7mm Taper Pinhole Lens			
Sync System	Internal			
IR Status	Under 10 Lux By CDS			
IR Power On	CDS Auto Control			
Usable Illumination	0 Lux/F2.0 (LED ON)			
S/N Ratio	≥ 48dB (AGC OFF)			
Gamma Correction	0.45			
Video Out	Composite Signal (1.0Vp-p, 75Ω)			
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec			
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec			
Operation Temperature	-10°C ~ +50°C RH95% Max			
Storage Temperature	-20°C ~ +60°C RH95% Max			
White Balance	Auto			
Power Source	DC12V 150mA			
Dimension	∅ 70(W) x40(H) x119(D)mm			
Weight	300g			