

# KIR-CN50

IR LED:  $\varnothing$  8X36PCS IR LED working

distance: 50M Built-in bracket 3-Axis direction bracket

Water resistance:IP66 Cable built-in bracket

Lens:: CS Lens 6mm/F2.0

Dimension:295(W)x120(H)x103(D)mm Weight:1.3Kg



Model	KIR-2362CN50	KIR-633CN50	KIR-2421CN50
Image Sensor	1/4"SHARP	1/3"SONY	1/4"SHARP
TV System			
Horizontal Resolution	560TV Lines Low Illumination	420TV Lines Low Illumination	420 TV Line Low Illumination
Pixels	PAL:752(H) $\times$ 582(V) NTSC:768(H) $\times$ 494(V)	PAL:500(H) $\times$ 582(V) NTSC:510(H) $\times$ 492(V)	
IR LED	$\varnothing$ 8 X36PCS		
IR Series Distance	50 M		
Lens	CS Lens 6mm/F2.0		
Sync System	Internal		
IR Status	Under 10 Lux By CDS		
IR Power On	CDS Auto Control		
Usable Illumination	0.001 Lux/F2.0	0.0005 Lux/F2.0	0.01 Lux/F2.0
S/N Ratio	$\geq$ 48dB (AGC OFF)		
Gamma Correction	0.45		
Video Out	Composite Signal (1.0Vp-p, 75 $\Omega$ )		
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec		
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec		
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max		
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max		
White Balance	Auto		
Power Source	DC12V 350mA		
Dimension	295(W)x120(H)x103(D)mm		
Weight	1300g		