



◆ SPECIFICATION

<b>Model NO.</b>	<b>NVRC436PM4FE500H</b>	
<b>Package</b>		
NVR	1x NVRC436P	
Camera	2 x IPSU20FE500 2x IPR25HFE00	
Cable	4x 20m CAT5e Cable	
Mouse	1xUSB 2.0 Mouse	
Hard Disk	No	
Adaptor	DC52V/1.25A	
Weight	7.3kg/SET	
<b>Camera Model</b>	<b>IPSU20FE500</b>	<b>IPR25HFE00</b>
Image Sensor	1/2.5" High-resolution CMOS Sensor	
Resolution	5MP	
Effective Pixels	2608(H)*1952(V)	
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG	
TV System	PAL/NTSC	
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec	
Minimum Illumination	0.01Lux	
S/N Ratio	≥52dB	
Scanning System	Progressive	
Video Output	Network	
Reset Button	Optional	
<b>Lens</b>		
Focus Length	3.6mm	
Focus Control	Fixed	
Lens Type	Fixed	
Pixels	5MP	

<b>Night Vision</b>		
Infrared LED	14μ x 18PCS	14μ x 20PCS
Infrared Distance	20M	25M
IR Status	Auto Control	
IR Power On	Auto Control	
<b>Network</b>		
Ethernet	RJ-45 (10/100Base-T)	
Wireless	/	
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP	
ONVIF	Support ONVIF 2.4	
P2P	YES, Support QR Code	
POE	Yes, Support IEEE 802.3af	
Video Delay	0.3S (Within the Lan)	
Main Stream 1	2592*1944@20fp 2560*1920@20fp	
Main Stream 2	2560*1440@25fp	
Main Stream 3	1920*1080@30fps 1280*720@30fps	
Sub Stream 1	720*480@15fps 720*480@30fps	
Sub Stream 2	/	
Sub Stream 3	/	
Tri Stream	/	
IE Brower	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari(lower than version 12)	
Smart Phone	iPhone, iPad, Android, Android Pad	
<b>Camera Features</b>		
Day/Night	Color/ B&W (IR-CUT )	
Image Config	Saturation/Brightness/Contrast/Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)	
Starlight	/	
Corridor Pattern	Support	
Defog Mode	/	
ROI	/	
BLC	Support	
HDR	/	
WDR	DWDR: 50dB	
Motion Detection	Support	
Privacy Masking	3 Rectangular Zone	
Recording Mode	NVR/CMS/Web	
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands,Czech, Vietnamese	
<b>Interface</b>		
Audio	Optional	

Alarm	/	
SD Card Slot	Optional, Support Max 512GB	
RS485	/	
<b>General</b>		
Housing	Metal , IP67	
Anti-cut Bracket	NO	YES
IR Cut Filter	YES	
Operation Temperature	-20℃ ~ +60℃ RH95% Max	
Storage Temperature	-20℃ ~ +60℃ RH95% Max	
Power Source	DC12V±10%, 750mA	DC12V±10%, 900mA
Dimension	φ93 x 74(H) mm	157(W) x 70(H) x 66(D)mm
Weight	400g	650g
<b>Model</b>	<b>NVRC436P</b>	
<b>System</b>		
Main Processor	ARM Cortex A7 Processor	
Operating System	Embedded LINUX	
<b>Video</b>		
Input	9CH (2592x1944, 2048x1536, 1920×1080, 1280×960, 1280×720, etc)	
Output	1 VGA, 1 HD	
<b>Audio</b>		
Input	/	
Output	1 Port 3.5mm(Linear, 1kΩ)	
Audio Bit Rate	64kbps	
Audio Compression standard	G711u, G711a, ADPCM_DVI4	
<b>Alarm</b>		
Sensor Input	NO	
Output	NO	
Motion Detection	9 Channel, MD Zones: 396 (22 × 18)	
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips, alarm output	
<b>Display</b>		
HD Output1	Resolution: 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
HD Output2	/	
VGA	Resolution:1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
Display Split	9CHxD1/8CHxD1/4CHxD1/1CHx1080P/1CHx3MP/1CHx4MP/1CHx5MP	
Digital Zoom	YES	
OSD	Camera Title, Time, Recording, Motion Detection, Event Alarm	

<b>Recording</b>	
Video Compression	H265/H264/H265+/H264+
Resolution	5MP(2592×1944),4MP(2688×1520/2560×1440),3MP(2048×1536),1080P(1920×1080),960P(1280×960),720P(1280×720),D1 (720×576/720×480)
Record Rate	PAL :5MP@9×25fp,4MP@9×25fp,3MP@9×25fp,1080P@9×25fp, 960P@9×25fp,720P@9×25fp, D1@9×25fp NTSC: 5MP@9×30fp,4MP@9×30fp,3MP@9×30fp,1080P@9×30fp, 960P@9×30fp, 720P@9×30fp, D1@9×30fp
Record Mode	Manual\Timer\Motion Detection\Smart Alarm
<b>Playback &amp; Backup</b>	
Local Sync Playback	1CH 5MP@30fps, 1CH 4MP@30fps, 2CH 3M@30fps, 4CH 1080P@20fps, 4CH 960P@30fps, 4CH 720P@30fps
Decode Capability	4CH 1080P@20fps
Remote Sync Playback	YES
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection,Event Alarm
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow Play, Full Screen, Frame Play ,Frame Rewind, Digital Zoom
Backup Mode	USB Device/Network
<b>Network</b>	
Interface	5 x RJ45 10M/100M Adaptive Ethernet Interface
Incoming Bandwidth	60MB
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, p2p
Onvif Version	Support Onvif 2.8
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
CMS Software	Support Windows 7/ Windows 8/Windows 10/MAC OS
Cloud Support(P2P)	Yes
Smart Phone	iPhone, iPad, Android, Android Pad
POE	4 x Independent 100Mbps POE Network Interfaces(Output PowerAT mode 30W, AF mode 15W per Interface), 45/78 line order, Total Power Output $\geq$ 50W, Support Plug and Play
WIFI	/
<b>Storage</b>	
Interface Type	1 SATA Hard Disk Interface (2.5"/3.5" SATA)
Capacity	Up to 8TB capacity
eSATA	/
<b>General</b>	
Language	Traditional Chinese, Simplified Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek, Vietnamese
USB Interface	2 USB 2.0 Interfaces
RS485	/
Power Supply	DC 52V/1250mA $\leq$ 6W (Without Hard Disk and POE)
Working Environment	-10~55°C/10~90%
Dimension(W×D×H)	260*215*43(mm)
Weight	2.0KG (without HDD)

**Cantonk(guangzhou) Corporation Limited**

F5,2# Building, No. 728, Kaichuang AVE., Economic & Technological Development Zone,Luogang District,510530 Guangzhou,China

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: [info@cantonk.com](mailto:info@cantonk.com)