



◆ SPECIFICATION

Model NO.	IPCF60HF200	IPCF60HL200	IPCF60HP200
Camera			
Image Sensor	F23	IMX307	IMX327
Main processor	Hi3516E	Hi3516C	Hi3516C
Resolution	2MP 1080P	2MP 1080P	2MP 1080P
Effective Pixels	1920(H)*1080(V)	1945(H)*1097(V)	1945(H)*1097(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI / MJPEG		
TV System	PAL/NTSC		
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec		
S/N Ratio	≥52dB		
Scanning System	Progressive		
Video Output	Network		
Reset Button	Optional		
Lens			
Focus Length	2.8-12mm		
Focus Control	Manual		
Lens Type	Manual		
Pixels	3M		
Night Vision			
Infrared LED	42μ x 4PCS		
Infrared Distance	40M		
IR Status	Auto Control		
IR Power On	Auto Control		
Network			
Ethernet	RJ-45 (10/100Base-T)		
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP		
ONVIF	Support ONVIF 2.4		
P2P	YES, Support QR Code		
POE	Optional, Support IEEE 802.3af		
Video Delay	0.3S (Within the Lan)		
Main Stream 1	1920*1080@20fps	2048*1536@15fps	2048*1536@15fps
Main Stream 2	1280*720@20fps	1920*1080@30fps	1920*1080@30fps
Main Stream 3	/	1280*720@30fps	1280*720@30fps
Sub Stream 1	720*480@20fps	720*480@15fps 720*480@30fps	720*480@15fps 720*480@30fps
Sub Stream 2	/	/	/
Sub Stream 3	/	/	/
Tri Stream	352*288@20fps	352*288@15fps 352*288@30fps	352*288@15fps 352*288@30fps
IE Brower	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari		
Smart Phone	iPhone, iPad, Android, Android Pad		
Camera Features			
Day/Night	Color/ B&W (IR-CUT)		
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering		
Full Starlight	/	/	/
Corridor Pattern	/	Support	Support
Defog Mode	Support	Support	Support
ROI	/	Support	Support
BLC	Support	Support	Support
HDR	/	/	/
WDR	Support	Support	Support
Motion Detection	Support	Support	Support
Privacy Masking	3 Rectangular Zone	3 Rectangular Zone	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web	NVR/NAS/CMS/Web	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands		
Interface			
Audio	Optional	Optional	Optional
Alarm	/	/	/
SD Card Slot	/	/	/
RS485	/	/	/
General			
Housing	IP66		
Anti-cut Bracket	YES		
IR Cut Filter	YES		
Operation Temperature	-20℃ ~ +60℃ RH95% Max		
Storage Temperature	-20℃ ~ +60℃ RH95% Max		
Power Source	DC12V±10%,1000mA		
Dimension	275(W) x 91(H) x 80(D)mm		
Weight	1.4kgs		

Cantank (guangzhou) Corporation Limited

Add. :2#, 4# Building, No. 728, Kaichuang AVE., Economic & Technological Development Zone,Luogang District,510530 Guangzhou,China

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantank.com> Email: info@cantank.com