



## ◆ SPECIFICATION

|                        |  |
|------------------------|--|
| Model NO.              | KLCBH5C5005XESH  |
| Video Output Mode      | AHD/TVI: 5M@20fps/12.5fps, 4M@30fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps |
| <b>Camera</b>          |  |
| Image Sensor           | 1/2.8" SONY Starvis Back-illuminated CMOS Sensor                       |
| Image Resolution       | 5M:2592*1944 4M:2560*1440 2M:1920*1080                                 |
| TV System              | PAL/NTSC   |
| Electronic Shutter     | Auto   |
| Minimum Illumination   | 0.005Lux   |
| Scanning System        | Progressive Scan   |
| <b>Lens</b>            |  |
| Focus Length           | Board Lens 6mm   |
| Focus Control          | Fixed  |
| Lens Type              | Fixed  |
| <b>Night Vision</b>    |  |
| IR Cut Filter          | YES  |
| Infrared LED           | 42μ x 2PCS   |
| Infrared Distance      | 30M  |
| IR Status              | AGC Auto Control   |
| <b>Camera Features</b> |  |
| Starlight              | YES  |
| Day/Night              | YES  |
| OSD Menu               | YES  |
| WDR                    | YES  |
| UTC                    | YES  |
| Noise Reduction        | AI-DNR   |
| White Balance          | AUTO / MANUAL  |
| Gain Control           | AUTO   |
| <b>General</b>         |  |
| Housing                | IP67   |
| Bracket                | NO   |
| Operation Temperature  | -10℃ ~ +60℃ RH95% Max  |
| Storage Temperature    | -20℃ ~ +60℃ RH95% Max  |
| Power Source           | DC12V±10%,500mA  |
| Dimension              | ∅ 136 x 148 (H) mm   |
| Weight                 | 1.7Kgs   |

Cantonk (Guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&amp;TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288

Fax No.: +86 20 66217166

Homepage: <http://www.cantonk.com>Email: [info@cantonk.com](mailto:info@cantonk.com)