



◆ SPECIFICATION

| Model NO.              | KBBB90HTC8005XESL  | KBBB90HTC8004XES                                    |
|------------------------|--|---|
| Video Output Mode      | AHD: 8M@15fps, 5M@20fps/12.5fps,<br>4M/2M@30fps/25fps;<br>CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps<br>TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps,<br>4M/2M@30fps/25fps; | AHD/TVI/CVI: 8M@15fps/12.5fps,<br>4M/2M@30fps/25fps |
| <b>Camera</b>          |  |   |
| Image Sensor           | 1/2.8" SONY Starvis Back-illuminated CMOS sensor   | 1/2.8" SONY CMOS sensor                             |
| Resolution             | 8M:3840*2160 5M:2592*1944<br>4M:2560*1440 2M:1920*1080   | 8M:3840*2160 4M:2560*1440<br>2M:1920*1080           |
| TV System              | PAL/NTSC   | PAL/NTSC  |
| Electronic Shutter     | Auto   | Auto  |
| Minimum Illumination   | 0.01Lux  | 0.01Lux   |
| Scanning System        | Progressive Scan   | Progressive Scan                                    |
| <b>Lens</b>            |  |   |
| Focus Length           | 2.7-13.5mm Motor Zoom  | 2.7-13.5mm Motor Zoom                               |
| Focus Control          | Auto   | Auto  |
| Lens Type              | Auto   | Auto  |
| <b>Night Vision</b>    |  |   |
| IR Cut Filter          | YES  | YES   |
| Infrared LED           | 42μ x 6PCS   | 42μ x 6PCS  |
| Infrared Distance      | 60M  | 60M   |
| IR Status              | AGC Auto Control   | AGC Auto Control                                    |
| <b>Camera Features</b> |  |   |
| Starlight              | /  | /   |
| Day/Night              | YES  | YES   |
| OSD Menu               | YES  | YES   |
| WDR                    | YES  | YES   |
| UTC                    | YES  | YES   |
| Noise Reduction        | 3DNR   | 3DNR  |
| White Balance          | AUTO / MANUAL  | AUTO / MANUAL                                       |
| Gain Control           | AUTO   | AUTO  |
| <b>General</b>         |  |   |

|                       |                            |                            |
|-----------------------|----------------------------|----------------------------|
| Housing               | IP67                       | IP67                       |
| Bracket               | YES                        | YES                        |
| Operation Temperature | -10℃ ~ +60℃ RH95% Max      | -10℃ ~ +60℃ RH95% Max      |
| Storage Temperature   | -20℃ ~ +60℃ RH95% Max      | -20℃ ~ +60℃ RH95% Max      |
| Power Source          | DC12V±10%,900mA            | DC12V±10%,900mA            |
| Dimension             | 220(W) x 105(H) x 109(D)mm | 220(W) x 105(H) x 109(D)mm |
| Weight                | 2.15Kgs (With bracket)     | 2.15Kgs (With bracket)     |

**Cantonk (guangzhou) Corporation Limited**

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: [info@cantonk.com](mailto:info@cantonk.com)