



◆ SPECIFICATION

| Model NO. | KLBAHTC800FKP | KLBAHTC800ESL | KLBAHTC800ES | KLBAHTC800FKE |
|------------------------|--|---|--|--|
| Video Output Mode | AHD/TVI: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 8M@15fps, 4M/2M@30fps/25fps | AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; | AHD/TVI/CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps | AHD: 8M@15fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps 4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps 4M/2M@30fps/25fps |
| Camera | | | | |
| Image Sensor | 1/2.5" CMOS sensor | 1/2.8" SONY Starvis Back-illuminated CMOS sensor | 1/2.8" SONY CMOS sensor | 1/2.5" CMOS sensor |
| Image Resolution | 8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080 | 8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080 | 8M:3840*2160 4M:2560*1440 2M:1920*1080 | 8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080 |
| TV System | PAL/NTSC | PAL/NTSC | PAL/NTSC | PAL/NTSC |
| Electronic Shutter | Auto | Auto | Auto | Auto |
| Scanning System | Progressive Scan | Progressive Scan | Progressive Scan | Progressive Scan |
| Lens | | | | |
| Focus Length | Board Lens 8mm | Board Lens 8mm | Board Lens 8mm | Board Lens 8mm |
| Focus Control | Fixed | Fixed | Fixed | Fixed |
| Lens Type | Fixed | Fixed | Fixed | Fixed |
| Night Vision | | | | |
| IR Cut Filter | YES | YES | YES | YES |
| Infrared LED | 42μ x6PCS | 42μ x6PCS | 42μ x6PCS | 42μ x6PCS |
| Infrared Distance | 60M | 60M | 60M | 60M |
| IR Status | AGC Auto Control | AGC Auto Control | AGC Auto Control | AGC Auto Control |
| Camera Features | | | | |
| Starlight | / | / | / | / |
| Day/Night | YES | YES | YES | YES/NO |
| OSD Menu | YES | YES | YES | YES |

| | | | | |
|-----------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| WDR | DWDR | YES | YES | DWDR |
| UTC | YES | YES | YES | YES |
| Noise Reduction | DNR | 3DNR | 3DNR | DNR |
| Coaxial Audio | / | / | / | YES(only TVI) |
| White Balance | AUTO / MANUAL | AUTO / MANUAL | AUTO / MANUAL | AUTO / MANUAL |
| Gain Control | AUTO | AUTO | AUTO | AUTO |
| General | | | | |
| Housing | IP67 | IP67 | IP67 | IP67 |
| Bracket | YES | YES | YES | YES |
| Operation Temperature | -10℃ ~ +60℃ RH95% Max | -10℃ ~ +60℃ RH95% Max | -10℃ ~ +60℃ RH95% Max | -10℃ ~ +60℃ RH95% Max |
| Storage Temperature | -20℃ ~ +60℃ RH95% Max | -20℃ ~ +60℃ RH95% Max | -20℃ ~ +60℃ RH95% Max | -20℃ ~ +60℃ RH95% Max |
| Power Source | DC12V±10%,900mA | DC12V±10%,900mA | DC12V±10%,900mA | DC12V±10%,900mA |
| Dimension | 313(W) x 109(H) x 106(D)mm | 313(W) x 109(H) x 106(D)mm | 313(W) x 109(H) x 106(D)mm | 313(W) x 109(H) x 106(D)mm |
| Weight | 1.85Kgs (With bracket) | 1.85Kgs (With bracket) | 1.85Kgs (With bracket) | 1.85Kgs (With bracket) |

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com