



◆ SPECIFICATION

Model NO.	KBTA30HTC500FEH	KBTA30HTC500ESH	KBTA30HTC500FPE
Video Output Mode	AHD/TVI:5M@20fps/12.5fps, 4M@30fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps	AHD/TVI: 5M@20fps/12.5fps, 4M@30fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps	AHD/TVI: 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 4M@30fps/25fps, 2M@30fps/25fps
Camera			
Image Sensor	1/3" CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor	1/3" CMOS Sensor
Image Resolution	5M:2592*1944 4M:2560*1440 2M:1920*1080	5M:2592*1944 4M:2560*1440 2M:1920*1080	5M:2592*1944 4M:2560*1440 2M:1920*1080
Electronic Shutter	AUTO	PAL/NTSC	PAL/NTSC
TV System	PAL/NTSC	Auto	Auto
Minimum Illumination	0.01Lux	0.005Lux	0.01Lux
Scanning System	Progressive Scan	Progressive Scan	Progressive Scan
Lens			
Focus Length	Board Lens 3.6mm	Board Lens 3.6mm	Board Lens 3.6mm
Focus Control	Fixed	Fixed	Fixed
Lens Type	Fixed	Fixed	Fixed
Night Vision			
IR Cut Filter	YES	YES	YES
Infrared LED	42μ x 2PCS	42μ x 2PCS	42μ x 2PCS
Infrared Distance	25M	25M	25M
IR Status	AGC Auto Control	AGC Auto Control	AGC Auto Control
Camera Features			
Starlight	/	YES	/
Day/Night	YES/NO	YES	YES
OSD Menu	YES	YES	YES
WDR	DWDR	YES	DWDR
UTC	YES	YES	YES
Noise Reduction	DNR	AI-DNR	DNR
White Balance	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL
Gain Control	AUTO	AUTO	AUTO
General			
Housing	IP67	IP67	IP67
Bracket	YES	YES	YES
Operation Temperature	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%,500mA	DC12V±10%,500mA	DC12V±10%,500mA
Dimension	170(W)x75(H)x77(D)mm	170(W)x75(H)x77(D)mm	170(W)x75(H)x77(D)mm
Weight	770g	770g	770g

Cantonek (Guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288

Fax No.: +86 20 66217166

Homepage: <http://www.cantonek.com>Email: info@cantonek.com