"Reliable Digital Security Products Manufacturer"





♦ SPECIFICATION

Model NO.	AC85
Camera	
Sensor	1/2.9" CMOS
Focal Length	3.2 mm
Aperture	F2.2
Optical Field of View	128° diagonal, 96° horizontal, 56° vertical
Minimum Illumination	0.01 lux
Audio	
Input	Built-in microphone
Output	Built-in speaker
Two-way Audio	Full duplex
Audio Compressing	AAC
Video	
Video Compressing	H.264, H.265
Lighting Frequency	50 Hz, 60 Hz
Frame Rate	15 fps
Maximum Resolution	1920 x 1080
Light Source For Night Vision	White light or infrared LED switchable
Network	
Wireless Standard	2.4 GHz Wi-Fi (IEEE 802.11 b/g/n)
Protocols Supported	TCP/IP, UDP/IP, DHCP, RTMP, MUTP
IP Address Type	Dynamic IP address
Recording	
Recording Method	Alarm triggered recording, and manual recording
Video Storage	Cloud storage, local Micro SD card (up to 128 GB), and mobile phone memory

Function		
Al Function	Human detection, vehicle detection, pet detection, package detection, activitiy zone	
Wake-up Method	PIR body induction wake-up and remote wake-up	
Alarm Notification	Alarm push by mobile app, white LED flashing and alarm sound warning	
Rotation Angle	355° pan, 90° tilt	
Indicator	RGB tri-color LED	
Battery		
Capacity	9000 mAh	
Removability	Unremovable	
Working Time	8 months (recording 20 pieces of 10-second video per day; pan & tilt unused)	
Standby Time	2 years	
Charging Voltage	5 V ±5%	
Charing Current	1.5 A	
Charging Time	15 hours	
Protection	Over-charge, over-discharge, over-current, short circuit and charging protection at high and low temperature	
Power Consumption	1	
Standby	1.68 mW	
Daytime Working	0.88 W	
Nighttime Working	2.23 W	
Interface		
Power	Micro USB	
Storage	Micro SD card	
Key	Power key and reset key	
Installation		
Installation Method	Wall mount, ceiling mount, desktop	
Bracket Type	1/4" universal screw hole	
Environment		
Dustproof and Waterproof	IP65	
Operating Temperature	-10 °C ~ 45 °C	
Storage Temperature	-20 ℃ ~ 60 ℃	
Prodoct dimension		
Dimension	120.2 mm × 101.1 mm × 158.3 mm (without bracket)	
Bare Weight	600 g	
Finished Weight	700 g	
Material	ABS + PC	
Color	White	
Certification		
Certification	CE, FCC, RoHS, WEEE, MSDS, UN38.3	