



◆ SPECIFICATION

Model NO.	KHKFW400W
Camera	
Image Sensor	1/3" Progressive Scan CMOS, Fullhan SOC, WDR,
Resolution	4MP@30fps /1080P@30fps/ 720P@30fps
Effective Pixels	2560*1440
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network/Wifi
Reset Button	Support
Lens	
Focus Length	3.7mm Taper Pinhole Lens
Focus Control	Fixed
Lens Type	Fixed
Pixels	4Mp
Night Vision	
Infrared LED	/
Infrared Distance	/
IR Status	/
IR Power On	/
Network	
Ethernet	RJ-45 (10/100Base-T)
Wireless	/
Protocol	TCP/IP,ICMP,HTTP,HTTPS,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP
ONVIF	ONVIF (PROFILE S,PROFILE G,PROFILE T) ,CGI

P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	4MP (2560*1440) @30fps (default) /4MP (2688*1512) @20fps
Main Stream 2	1080P (1920*1280) @30fps / 720P (1280*720) @30fps
Sub Stream 1	720P (1280*720) @30fps (default) D1 (720*480) @30fps
Sub Stream 2	/
IE Brower	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari(lower than version 12)
Smart Phone	iPhone, iPad, Android, Android Pad

Camera Features

Day/Night	Color/ B&W
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control),Video Tampering
Full Color	/
Corridor Pattern	Support
Defog Mode	Support
ROI	Support
BLC	Support
WDR	/
Motion Detection	HDR: 120dB
Privacy Masking	Support
Recording Mode	3 Rectangular Zone
Language	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands,Czech, Vietnamese

Interface

Audio	Audio IN/OUT
Alarm	1ch Alarm In/1ch Alarm Out (Support humanoid-based enhanced motion detection to avoid false positives caused by non-humanoids)
SD Card Slot	Support Max 512GB
RS485	Support

General

IR Cut Filter	NO
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, DC12V 1A
Dimension	36(W) x 36(H) x33(D)mm
Weight	300g

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com